

# CNC 15000 HYDRAULIC WINCH



MOBILE AND INDUSTRIAL HYDRAULIC

- \* MAXIMUM PULL FORCE: 15.000 kg
- \* MAXIMUM ROPE LENGTH: 50 mt
- \* MAXIMUM ROPE DIAMETER: 18 mm
- \* HYDROMOTOR: WR-200 cc
- \* MAXIMUM OPERATING PRESSURE: 170 bar
- \* MAXIMUM PUMP FLOW: 60 lt/min
- \* CONVERSION RATIO: 35/1
- \* RECOMMENDED OIL: 80 W / 1.5 lt
- \* PRODUCT WEIGHT: 185 kg
- \* LONG-LIFE HYDRAULIC BRAKE SYSTEM POWERED BY MULTIPLE DISCS.
- \* THROUGH HEAT TREATMENT EXTRA RAINFORCE PLANETARY GEAR SYSTEM MADE OF SPECIAL STEEL
- \* HIGH STRENGTH CASTING BODY AND CAST ROLLER.
- \* HIGH TORQUE HYDROMOTOR.



NUMBER OF ROPE WRAPS	PULL CAPACITY	ROPE PULLING CAPACITY	ROPE LENGTH
1. WRAP	15,000 KG	DK / 3MT	6MT
2. WRAP	13,200 KG	DK / 4,5MT	15MT
3. WRAP	11,600 KG	DK / 5,5MT	24MT
4. WRAP	10,200 KG	DK / 6,5MT	37MT
5. WRAP	9,000 KG	DK / 7,5MT	50MT

**ATTENTION:**

- \* ALWAYS LEAVE THE FIRST FIVE WRAPS ON.
- \* DO NOT FORGET TO OPEN THE A-B TANK LINE FROM THE ROPE DRUM CONTROL VALVE.
- \* DO NOT FORGET TO OPEN HYDROMOTOR LEAK LINE.

