## CNC 18000 HYDRAULIC WINCH



\* MAXIMUM PULL FORCE: 18.000 kg

\* MAXIMUM ROPE LENGTH: 45 mt

\* MAXIMUM ROPE DIAMETER: 18 mm

\* HYDROMOTOR: WP-200 cc

\* MAXIMUM OPERATING PRESSURE: 170 bar

\* MAXIMUM PUMP FLOW: 60 lt/min

\* CONVERSION RATIO: 36/1

\* RECOMMENDED OIL: 80 W / 1.5 It

\* PRODUCT WEIGHT: 200 kg (Without rope)



- \* LONG-LIFE HYDRAULIC BRAKE SYSTEM POWERED BY MULTIPLE DISCS.
- \* THROUGH HEAT TREATMENT EXTRA RAINFORCE PLANETARY GEAR SYSTEM MADE OF SPECIAL STEEL
- \* HIGH STRENGTH CASTING BODY AND CAST ROLLER.
- \* HIGH TORQUE HYDROMOTOR
- \* HYDRAULIC BRAKE SYSTEM

NUMBER OF ROPE WRAPS	PULL CAPACITY	ROPE PULLING CAPACITY	ROPE LENGTH
1. WRAP	18,000 KG	MIN/3,9MT	8 MT
2. WRAP	16,200 KG	MIN/4,8MT	18 MT
3. WRAP	14,580 KG	MIN/5,7MT	31 MT
4. WRAP	13,120 KG	MIN/6,7MT	45 MT

## ATTENTION!

- \*ALWAYS LEAVE THE FIRST FIVE WRAPS ON.
- \*DO NOT FORGET TO OPEN THE A-B TANK LINE FROM THE ROPE DRUM CONTROL VALVE.
- \*DO NOT FORGET TO OPEN HYDROMOTOR LEAK LINE.



