

# CNC 4200 HYDRAULIC WINCH



MOBILE AND INDUSTRIAL HYDRAULIC

- \* MAXIMUM PULL FORCE: 4.200 kg
- \* MAXIMUM ROPE LENGTH: 53 mt
- \* MAXIMUM ROPE DIAMETER: 12 mm
- \* HYDROMOTOR: WP-200 cc
- \* MAXIMUM OPERATING PRESSURE: 175 bar
- \* MAXIMUM PUMP FLOW: 60 lt/min
- \* CONVERSION RATIO: 6,2/1
- \* RECOMMENDED OIL: 80 W / 0.7 lt
- \* PRODUCT WEIGHT: 80 kg
- \* LONG-LIFE HYDRAULIC BRAKE SYSTEM POWERED BY MULTIPLE DISCS.
- \* THROUGH HEAT TREATMENT EXTRA RAINFORCE PLANETARY GEAR SYSTEM MADE OF SPECIAL STEEL
- \* HIGH STRENGTH CASTING BODY AND CAST ROLLER.
- \* HIGH TORQUE HYDROMOTOR
- \* HYDRAULIC BRAKE SYSTEM



NUMBER OF ROPE WRAPS	PULL CAPACITY	ROPE PULLING CAPACITY	ROPE LENGTH
1. WRAP	4,200 KG	MIN/14,6MT	5,5 MT
2. WRAP	3,780 KG	MIN/18MT	12 MT
3. WRAP	3,400 KG	MIN/22MT	20 MT
4. WRAP	3,000 KG	MIN/25,4MT	30 MT
5. WRAP	2,750 KG	MIN/29MT	40 MT
6. WRAP	2,480 KG	MIN/33MT	53 MT

**ATTENTION!**

- \*ALWAYS LEAVE THE FIRST FIVE WRAPS ON.
- \*DO NOT FORGET TO OPEN THE A-B TANK LINE FROM THE ROPE DRUM CONTROL VALVE.
- \*DO NOT FORGET TO OPEN HYDROMOTOR LEAK LINE.

