

# CNC 5200 HYDRAULIC WINCH



MOBILE AND INDUSTRIAL HYDRAULIC

- \* MAXIMUM PULL FORCE: 5.200 kg
- \* MAXIMUM ROPE LENGTH: 53 mt
- \* MAXIMUM ROPE DIAMETER: 12 mm
- \* HYDROMOTOR: WP-250 cc
- \* MAXIMUM OPERATING PRESSURE: 175 bar
- \* MAXIMUM PUMP FLOW: 60 lt/min
- \* CONVERSION RATIO: 6,2/1
- \* RECOMMENDED OIL: 80 W / 0.7 lt
- \* PRODUCT WEIGHT: 80 kg
- \* LONG-LIFE HYDRAULIC BRAKE SYSTEM POWERED BY MULTIPLE DISCS.
- \* THROUGH HEAT TREATMENT EXTRA RAINFOURCE PLANETARY GEAR SYSTEM MADE OF SPECIAL STEEL
- \* HIGH STRENGTH CASTING BODY AND CAST ROLLER.
- \* HIGH TORQUE HYDROMOTOR.



NUMBER OF ROPE WRAPS	PULL CAPACITY	ROPE PULLING CAPACITY	ROPE LENGTH
1. WRAP	5,200 KG	MIN/11,8MT	5,5 MT
2. WRAP	4,680 KG	MIN/14,8MT	12 MT
3. WRAP	4,200 KG	MIN/18MT	20 MT
4. WRAP	3,800 KG	MIN/20,5MT	30 MT
5. WRAP	3,400 KG	MIN/23,5MT	40 MT
6. WRAP	3,070 KG	MIN/27MT	53 MT

**ATTENTION!**

- \*ALWAYS LEAVE THE FIRST FIVE WRAPS ON.
- \*DO NOT FORGET TO OPEN THE A-B TANK LINE FROM THE ROPE DRUM CONTROL VALVE.
- \*DO NOT FORGET TO OPEN HYDROMOTOR LEAK LINE.

